3. Specifications

Television System	CS	PAL/SECAM-B/G/D/K,L,I, NTSD-M	
Antena Input	-	75ohms, Coaxial Cable	
Power	Consumption	130W(Applied When 29" Flat)	
	Requirements	220V Only	
		Free Voltage	Not Present R815
	Frequency	50/60Hz	
Sound	Output	15W x 2CH	29Inch
		10W x 2CH	21Inch
		5W x 2CH	
		30W x 2CH	29Inch Normal woofer
		20W x 2CH	21Inch Flat woofer
	Effect	Virtual Dolby	Option
		Trubo Sound	
		Pseudo Stereo	
		Woofer Sound	
Jacks	Front(AV2)	RCA Input	
		S-VHS	Option
	BACK	Head-Phone	
		RCA99(AV2 Input/Out)	
		2Scart Input/OUtput	AV1: Scart I/O, RGB Input, RF Out AV2: Scart I/O, Monitor Out
		DVD Input(YPbPr)	Option
		AV2 Monitro Audio Output	Option
		S-VHS	Option
		Woofer Output	2CH

Specifications for Model Name (Ex. CS29A6??8X/HAC)

Specifications for Model Name (Ex. CS29A6??8X/HAC)

	Function	NOTE
N	NICAM	"NICAM" means that A2 STEREO + NICAM
P	2 TUNER PIP	
PF	2 TUNER PIP, NICAM, TTX	
PT	2 TUNER PIP, A2 STEREO, TTX	
PW	2 TUNER PIP, A2 STEREO	
MT	2 TUNER MULTI PIP, A2 STEREO,	
NT	NICAM, TTX	
WT	A2 STEREO, TTX	
GW	1 TUNER PIP, A2 STEREO, TTX	

MEMO